

Absorbent 10

Technic Eco Services sa
62, Avenue de la Liberté
L-1930 Luxembourg
Luxembourg
Tel: +352 26 008 248
Fax: +352 26 008 249
E-mail: info@teslux.eu

Product Highlight

OVERVIEW: Industrial absorbent material based on calcinated minerals without chemical additives. Applicable to absorb all kind of gas odorants (THT , TBM , TDM ...)

CHARACTERISTICS:

- High absorbent capacity.
- 1 Kg Absorbent 10 can absorb one liter of gas odorant.
- Dustfree.

ADVANTAGES:

The material can be reused several times which reduces your waste. This makes the product,

- Despite the somewhat more expensive price, very cost-effective.
- This product has a non-skid and anti-slip effect.
- Leaves no residues.
- Absorbent 10 can be used on all types of floors.

APPLICATIONS: Strew the absorbent material all over the waste. Then sweep with a stiff broom until the dirt becomes visible absorbed. Pick it up and throw it in a collector bucket. The darker the granules, the more liquid they have absorbed. The absorbent can be reused until it has been saturated.

PRECAUTIONS: Applicable to absorb almost all kinds of gas odorants except peroxides and other strong oxidizable chemicals.

SAFETY: Refer also appropriate MSDS before handling and use.

Packaging: 1 bag : 10 kg
1 pallet : 56 bags

Specifications:

| | |
|-----------------------------|---------------------------------|
| Chemical notation | : Al_2SiO_2 |
| Granule-seize distribution: | : 24/48 Mesh (0.32 - 0.80 mm) |
| Dumping weight | : ± 590 g/l |
| pH value | : neutral |
| Water-absorption | : $135\% \pm 10$ |
| Oil-absorption | : $115\% \pm 10$ (Westinghouse) |